

# CapaClean



High quality interior finish, zero VOC.



## Properties /

## Usage /

## Tech data / Ingredients

## Applications / Tools

## Packing /

## Storage /

## Product Description

- ▶ Dry paint film with good washability resistance
- ▶ Special effect mildew formula, can effectively inhibit the growth of mold.
- ▶ Good opacity (superior products, according to GB / T 9756-2009 "synthetic resin emulsion interior wall paint").
- ▶ Odorless, in line with environmental requirements (VOC not detected, according to GB 18582-2008) "interior decoration.
- ▶ Repair materials interior wall paint harmful substances "(water-based wall paint).
- ▶ Dense paint film to reduce dirt adhesion.

Specially designed for interior decoration of luxurious apartment, suitable for residential, hotel, school, office building and other projects through the table Interior treatment of the wall. Can also be used in kindergarten, hospital, the elderly center for easy cleaning.

Acrylic emulsion, titanium dioxide, extenders, pigments, additives and deionized water.

Matte to low light, depending on the colour

Theoretical coverage 12.5 m<sup>2</sup>/L/Coat

Drying time Surface dry : 1hr (Air temperature: 23°C, Relative humidity: 50%)

Recoat : 12hr (Air temperature : 23°C, Relative humidity: 50%)

Volume solid 43%

Density 1.46 kg/L (influence proportion after color mixing)

Weather Resistance Good

Safety No added Pb and Hg

Colour White, colour-adjustable (according to 3D color card)

Paint brush, roller, spray gun

Thinner Dilute with clear water, dilute ratio of 5-10%

Wet film thickness Theoretical value: about 80 microns (1 coat)

Dry film thickness Theoretical value: about 35 microns (1 coat)

Conditions Air temperature: > 8°C , Relative humidity: <85%

Cleaning Rinse with fresh water immediately after application

Notes Don't apply under direct sunlight

15L

Keep in cool and dry place, avoid from frost

## Application

Surface preparations /  
Interior wall putty

1. Putty completely dry, grinding with fine sandpaper to remove dust
2. If the request is more durable, brush the diluted CapaSol SF before scraping the putty.
3. Putty should not be too soft.

Powdered surface

1. Remove dust as much as possible.
2. Brush the diluted CapaSol SF.

Moldy surface

1. Wipe the mold.
2. Brush again wash water, to be dry 24-48 hours, brush once again dilute the Dragon Fort seal primer.

Method of application /

- a. Read the instruction before application.
- b. Stir well before applying.
- c. Follow the instructions to add a proper amount of water. Do not overdose and stir evenly.
- d. Avoid over loading of paints on tools.
- e. Wash tools immediately after applications
- f. Do not fill the thinned paints into the packing drum.

Painting system /

After the surface treatment on the base surface, direct construction of Capa Primer, and then the construction of all kinds of Capa interior wall paint

## Advice

**SHE** /

This product meets the National Standard GB/T 9756-2009 "synthetic resin emulsion interior wall paint"; GB18582-2008 "indoor decoration decoration material inside wall coating harmful material limit" (water based wall paint). It is our principle to provide high standard of safety, health and environmental information. We will provide materials safety data free of charge as well as related information.

**Information** /

1. Please follow BS6150:1991 standard for architectural coating applications and BS8000:1989 for site instruction.
2. Shelf life : 24 months in unopened condition.
3. Above information is provided by Caparol (China) Ltd, we ensure the accuracy of the information provided. However due to the application conditions are not controllable, there may be variance in end result.
4. For further enquiry, please contact our company. Please make sure the information is updated before application. The above information was released in Jan 2018. Caparol (China) Ltd. reserve the right to update the above information without notice in advance.

**Trademark declaration** /  
**Company address** /

Caparol is the trademarks belong to DAW SE.

CAPAROL (CHINA) LTD.

25F, Block B Kingboard Square, 505 Guangming Road,

Huaqiao Economic Development Zone, Kunshan, Jiangsu, 215332

**Tel** /

0512-86183333

**Fax** /

0512-86183311

www.dawchina.com