



Caparol Nano Clean

Long lasting dust repellent for facades



Properties /

Usage /

Tech data / Ingredients

Gloss level

Theoretical coverage

Drying time

Volume solid

Density

Safety

Colour

Applications / Tools

Thinner

Wet film thickness

Dry film thickness

Conditions

Cleaning

Notes

Packing /

Storage /

Product Description

- ▶ New technology for facadetreatment, longlastingclean.
- ▶ Sub-micro particules fill the porous of the topcoat.
- ▶ Polar in nature, allow water to flow evenly under the dust.
- ▶ Reduce tear marks.
- ▶ Pink coloured, clear when dried, avoid leaving out area.

Suitable for all Caparol matt facades, stone paints and textured paints.

Silicate particules, additives and de-ionized water.

Matt

15-20 m²/L/Coat

Surface dry : 1-2 hr (Air temperature: 23°C, Relative humidity: 50%)

Recoat : 2-4 hr (Air temperature : 23°C, Relative humidity: 50%)

3%

1.02 kg/L

No added heavy metal

Pink coloured, clear when dry

Rollers or low pressure spray gun

Not necessary

N/A

N/A

Air temperature: 8°C or above, Relative humidity: <85%

Rinse with fresh water immediately after application

1. Can be applied on matt Waterborne paints (light colours)

2. Not suitable for dark colours

3. Not suitable on old wall surface

4. Must be coated evenly

20L

Keep in cool and dry place, avoid from frost

Application

Surface preparations /

1. Remove all loose materials.
2. Apply Caparol Nano Clean once the paints dried.

Method of application /

- a. Read the instruction before application.
- b. Stir well before applying.
- c. Apply Nano clean evenly, avoid leaving out painting.
- d. Avoid over loading of paints on tools.
- e. Wash tools immediately after applications
- f. Do not fill the thinned paints into the packing drum.

Painting system /

Caparol exterior coatings/CapaStone/CapaTex+CaparolNano Clean (2 coats)

Advice

SHE /

This product complies with National Standard GB/T9755-2014 .
It is our principle to provide high standard of safety, health and environmental information. We will provide materials safety data free of charge as well as related information.

Information /

1. Please follow BS6150:1991 standard for architectural coating applications and BS8000:1989 for site instruction.
2. Shelf life : 24 months in unopened condition.
3. Above information is provided by Caparol (China) Ltd, we ensure the accuracy of the information provided. However due to the application conditions are not controllable, there may be variance in end result.
4. For further enquiry, please contact our company. Please make sure the information is updated before application. The above information was released in Feb 2017. Caparol (China) Ltd. reserve the right to update the above information without notice in advance.

Trademark declaration /
Company address /

Caparol is the trademarks belong to DAW SE.

CAPAROL (CHINA) LTD.

25F, Block B Kingboard Square, 505 Guangming Road,
Huaqiao Economic Development Zone, Kunshan, Jiangsu, 215332

Tel /

0512-86183333

Fax /

0512-86183311

www.dawchina.com